


全方位門禁讀頭

多款門禁讀頭，提供全方位的運用



多輸出格式

AR-101U/AR-725K/AR-725U/
AR-721U/AR-331K/AR-331U/AR-661U



雙頻

AR-101U



體積小

AR-101U/AR-721U



觸碰式背光面板

AR-725K/AR-725U/AR-331K/AR-331U



金屬材質機身

AR-331K/AR-331U



防塵/防水等級

IP55: AR-725K/AR-725U
IP56: AR-721U/AR-725U/
AR-331K/AR-331U/AR-661U



全方位門禁讀頭

多款門禁讀頭，提供全方位的運用

讀頭
AR-101U



長距離讀頭
AR-661U



讀頭
AR-721U



按鍵型讀頭
AR-721K



感應頻率	13.56MHz	13.56MHz+125kHz	125kHz	125kHz	13.56MHz	125kHz	13.56MHz
工作電壓	9-24VDC		12-16VDC	9-24VDC		9-24VDC	10-24VDC
資料傳輸標準	EM Standard	-ISO14443A (可選購) -MIFARE -DESFire	EM Standard	EM Standard	-ISO14443A (可選購) -ISO15693 -ISO7816 -DESFire -NFC	EM Standard	-ISO14443A (可選購) -ISO15693 -DESFire -PSAM -NFC
感應距離 <small>取決於TAG或卡片</small>	2-5cm	1-3cm	33-60cm	6-12cm	3-8cm	10-18cm	3-8cm
讀/寫功能	Read Only	Read/Write	Read Only	Read Only	Read/Write	Read Only	Read/Write
消耗功率	<1W		<3W	<1W		<1W	
通訊介面	Wiegand24/36, ABA-II, ASYNC		Wiegand, ABA-II, ASYNC	Wiegand, ABA-II, ASYNC		Wiegand, ABA-II, ASYNC	
傳輸速率	9600 bps(N,8,1)		9600 bps(N,8,1)	9600 bps(N,8,1)		9600 bps(N,8,1)	
環境溫度	-20 °C to +60 °C		-20 °C to +60 °C	-20 °C to +60 °C		-20 °C to +60 °C	
按鍵	No		No	No		Yes	
指示器	1組雙色LED+1組蜂鳴器		3組LED & 1組蜂鳴器	1組雙色LED+1組蜂鳴器		1組雙色LED+1組蜂鳴器	
防水指數	NO		IP56	IP56(選購)		No	
外殼材質	ABS		ABS	ABS		ABS	
顏色	深灰		深灰	標準: 黑/灰/銀 選購: 白/藍/綠/黃/橘/紅		深灰/銀	
外型尺寸(mm)	37(L)X37(W)X31(H)		228(L)X228(W)X38(H)	81(L)X43(W)X18(H)		111(L)X77(W)X26(H)	
重量(g)	26±10		1000±50	40±10		90±10	

金屬讀頭
AR-331U



金屬按鍵讀頭
AR-331K



讀頭
AR-725U
AR-725U-M



按鍵型讀頭
(觸碰式背光)
AR-725K
AR-725K-M



感應頻率	125kHz	13.56MHz	125kHz	13.56MHz	125kHz	13.56MHz	125kHz	13.56MHz
工作電壓	9-24VDC		9-24VDC		9-24VDC		9-24VDC	
資料傳輸標準	EM Standard	-ISO14443A (可選購) -ISO15693 -DESFire -PSAM -NFC	EM Standard	-ISO14443A (可選購) -ISO15693 -DESFire -PSAM -NFC	EM Standard	-ISO14443A (可選購) -ISO15693 -DESFire -PSAM -NFC	EM Standard	-ISO14443A (可選購) -ISO15693 -DESFire -PSAM -NFC
感應距離 <small>取決於TAG或卡片</small>	3-7cm	1-3cm	3-7cm	1-3cm	5-15cm(725U) 5-8cm(725U-M)	3-8cm(725U) 3-5cm(725U-M)	5-15cm(725K) 5-8cm(725K-M)	3-8cm(725K) 3-5cm(725K-M)
讀/寫功能	Read Only	Read/Write	Read Only	Read/Write	Read Only	Read/Write	Read Only	Read/Write
消耗功率	<1W		<1W		<1W		<1W	
通訊介面	Wiegand, ABA-II, ASYNC		Wiegand, ABA-II, ASYNC		Wiegand, ABA-II, ASYNC		Wiegand, ABA-II, ASYNC	
傳輸速率	9600 bps(N,8,1)		9600 bps(N,8,1)		9600 bps(N,8,1)		9600 bps(N,8,1)	
環境溫度	-20 °C to +60 °C		-20 °C to +60 °C		-20 °C to +60 °C		-20 °C to +60 °C	
按鍵	No		Illuminated Touch-panel		No		Illuminated Touch-panel	
指示器	2組LED+1組蜂鳴器		2組LED+1組蜂鳴器		3組LED+1組蜂鳴器		1組雙色LED+1組蜂鳴器	
防水指數	IP56		IP56		IP55 / IP56(選購)		IP55	
外殼材質	鋅合金		鋅合金		鋅合金+PC(725U-M) / PC(725U)		鋅合金+PC(725K-M) / PC(725K)	
顏色	Chrome		Chrome		標準: 黑/灰/銀 選購: 白/藍/綠/黃/橘/紅		標準: 黑/灰/銀 選購: 白/藍/綠/黃/橘/紅	
外型尺寸(mm)	154(L)X51(W)X21(H)		154(L)X51(W)X21(H)		79(L)X110(W)X26(H) (725U) 125(L)X89(W)X30(H) (725U-M)		79(L)X110(W)X26(H) (725K) 125(L)X89(W)X30(H) (725K-M)	
重量(g)	270±10		270±10		150±10(725U) / 400±10(725U-M)		150±10(725K) / 400±10(725K-M)	

產品架構

