Hardware Specifications

Gateway

Home Gateway / F-GW-600-ZEW

- ZigBee and Wi-Fi communication
- Supports 16 devices connection

Cloud Plug

Wireless Plug

- Electrical rating of 10V/13A/1430W
- ZigBee communication

Smart Socket 110V / F-SK-1101-Z

- Electrical rating of 110V/15A/1650W
- ZigBee communication

Smart Socket 220V / F-SK-2201-Z

- Electrical rating of 220V/15A/3300W
- ZigBee communication

Universal Socket / F-USK-220X-Z

- Changeable socket and plug
- ZigBee communication

Smart Strip / F-SK-1104-Z

- Four Individual power measurement
- Electrical rating of 110V/15A/1650W
- ZigBee communication

Universal Strip / FPS-Z-ZM-3E2A

- Three outlets
- Two USB ports
- ZigBee communication

Embedded Smart Outlet / FP-Z-QM-1U2A

- Universal Outlet
- Two USB ports
- ZigBee communication

Cloud Sensor

CO Detector / SG02-CO

- 0 ~ 2,000 ppm measurement
- 80 dB voice alarm
- ZigBee communication

CO2 Detector / SG02-CO2

- 0 ~ 10,000 ppm measurement
- 80 dB voice alarm
- ZigBee communication

Gas Detector / SG02-GS

- 10% LEL natural gas ; 15% LEL liquefied petroleum gas
- 80 dB voice alarm
- ZigBee communication

Wireless Thermo-Hygrometer / SG110-A

- Batteries power supply
- -10°C~45°C measurement
- ZigBee communication

Thermo-Hygrometer / PAT04-1B

- 1700 mA lithium battery
- maximum 80% Relative humidity
- ZigBee

6 in 1 Air Mentor / 8096-AP

- TVOC, PM 2.5, PM 10, CO2, RH, Temp
- Bluetooth communication
- Expandable with BT to Wi-Fi bridge

4 in 1 Air Mentor / 8096-AM

- TVOC, PM2.5, RH, Temp
- Bluetooth communication
- Expandable with BT to Wi-Fi bridge

PIR / WZB-SPM-05

- Batteries power supply
- 9m measurement range
- ZigBee communication

Smart PIR / PST03-B

- 12m measurement range
- ZigBee communication

Meter

Duel CT Meter / F-USK-1602MU-Z

- 220V circuit measurement
- ZigBee communication

Single CT Meter / F-USK-1601MU-Z

- 110V circuit measurement
- ZigBee communication

Controller

IR Controller / F-IRC-W

- Embedded eight IR transmitters
- Wi-Fi communication

Smart Button / PSR06

- Set customized control
- Replace mobile App

Siren



Smart Network System Institute, SNSI 7F., No.133, Sec. 4, Minsheng E. Rd., Songshan Dist Taipei City 105, Taiwan (R.O.C.)

- Siren / PSE03-1
- 110 dB voice alarm
- ZigBee communication

III INSTITUTE FOR INFORMATION INDUSTRY





Connectivity | Management | Engagement



E-mail : sales@insnergy.com Web : www.insnergy.com Tel: +886-2-6600-0996

In-Snergy Family take care IoT for you

API

Integrate with your enterprise application via InSnergy API seamlessly



Module

Transforming your traditional device to smart connected appliance





Application

Manage your device right from mobile and web application



÷



